

PROTECT breathable self-adhesive cover fleece ATC

160 g/m²

Art.-Nr.: TD 10721
1m x 25m, 25m²

Art.-Nr.: TD 10764
1m x 50m, 50m²

Blue breathable self-adhesive floor protection fleece



impermeable



adhesive



100 % residue-free



open to diffusion
breathable

Data sheet

Main Description: A multi-layered, multi-use and reusable protection mat for your job site.

Advantages: resistant, waterproof, anti slip, easily applied/time saving, no tape needed, self-adhes

Area of Use: Protect your valuable floors and hard surfaces against tools, sharp debris, paint, liquids, dirt and other hazards. Suitable for flooring, stairs, counter tops, appliances, tables, furniture, plumbing fixtures and a variety of other applications.

Usage & care instructions

- 1) Ensure you turn off floor heating before laying the fiber .
- 2) Clean the underlaying surface for better adhesion and to maximize reusable adhesion.
- 3) The product should be laid down with an overlap of 4 in / 10 cm.
- 4) Protect against direct sun exposure for prolonged periods of time.
- 5) Ensure surfaces to be protected are dry before applying this product.
- 6) Do not use on surfaces that have been treated with any solvent-based products before they have been properly cured per the manufacturer's guidelines and no longer emit solvent vapor.
- 7) Avoid placing heavy objects directly on the surface protection mat for prolonged periods of more than 24 hours.
- 8) Taping down the start and end of the rolls is recommended.
- 9) To ensure clean removal and possible residual adhesive, this product should not be left on any unfinished surface for more than 60 consecutive days.
- 10) Ensure floor heating is turned off when using the fiber.
- 11) The fiber is not recommended for cement or concrete floors. The adhesive may leave residue and/or fail to adhere as effectively on cement surfaces due to it's high mineral and polymer content.

Technical Data:

Product Construction:

Material-Bottom	PET fiber
Material-Top	Breathable PE-film
Type of adhesive	water-base cement
Dimension	1 x 25m / 1 x 50m
Thickness	1,5mm
Weight	160g/m ²
Colour	Blue

Properties/Performance Values:

Elongation-MD	13,50 %
Elongation-CD	45,20 %
Break-strength-MD	61.9 N/50mm
Break strength-CD	72.2 N/50mm
Water vapor permeability	1800g/m ² .24h
Ambient humidity	10%~90%
Recommended application temperature	-22°C~55°C
Application time	14 days
Storage time	1 year

Warning:

- 1) The application time may vary depending on the type of floor, type of heating, ambient temperature etc. It is up to the customer to test the product on an unvisible part before proceeding with a complete installation.
- 2) Keep all flame and heat sources away from this product.



CONTACT

